

## VAPOUR JET REFRIGERATOR/HEAT PUMP R853



Year 1  
study

### Features

- Enables demonstration and investigation of the combined Rankine and Vapour Compression Cycle
- Is an example of a refrigerator or heat pump driven by a Heat Input as opposed to the more usual work input
- Uses hot water as the 'high grade' heat source, thus limiting the maximum temperature to 100°C
- Evaporation and Condensation may clearly be seen through glass cylinders
- As a heat pump, the unit shows approximately the same primary energy ratio as a work-driven heat pump
- All important components are mounted on the front panel and quickly responds to a change in operating conditions.
- Optional Solar Panels available

### Description

The unit may be regarded as a combined heat engine and a refrigerator/heat pump. The system powering the refrigerator/heat pump works on the well-known Rankine cycle (frequently used in steam power plants.) In this cycle the unit takes in heat at a very modest temperature (about 90°C) and rejects heat at the condenser temperature (about 30°C). The work output of this engine is in the form of the kinetic energy of a jet instead of shaft work as is normal with a Rankine cycle. The refrigerator/heat pump operates on the Vapour Compression Cycle and uses the output of the Rankine Cycle (i.e. the kinetic energy of the jet). It takes in heat at a low temperature in an evaporator and rejects heat at a higher temperature using the same condenser as the engine. Both the Rankine Power Plant Cycle and the Vapour Compression/Heat Pump Cycle are included in most courses of study for young engineers. The Hilton Vapour Jet Refrigerator/Heat Pump R853 demonstrates practically, the potential of combining these cycles so that a heat pump or refrigerator can be run from a heat output.

#### Related Laws/Applications

- Refrigeration & Air Conditioning
- Building Services
- Mechanical Engineering
- Plant and Process Engineering
- Energy Conservation
- Energy Management
- Chemical Engineering
- Food Technology
- Marine Engineering
- Agriculture Engineering

#### Learning capabilities

- Analysis of the combined Rankine and Vapour Compression Cycle.
- Demonstration of the characteristics of an ejector or thermo compressor.
- Production of performance curves as a refrigerator and comparison with ideal Rankine/Vapour Compression cycle.
- Production of performance curves as a heat pump and comparison with ideal Rankine/Vapour Compression Cycle.
- Investigation of entrainment mass ratio at various pressures.
- Demonstration of 'adiabatic' mixing of hot and cold vapour.
- Demonstration of 'adiabatic' throttling.

#### Technical Specification

- Panel: High quality GRP.
- Steam Generator: Rectangular GRP insulated vessel fitted with 1.5kW immersion heater and containing the refrigerant vapour generator.
- Refrigerant Vapour Generator: stainless steel shell, Ø75mm x 200(L) mm, with sight glass and pre-heating coil.
- Ejector Nozzle: Convergent-divergent, throat diameter 1.7mm.
- Compressor Diffuser: With combining cone, parallel and divergent portions.
- Evaporator: Thick walled glass cylinder, incorporating a 500W heater controlled by a variable transformer and a float type expansion valve.
- Condenser: Thick walled glass cylinder fitted with water cooling coil. Surface area of coil: 0.1m<sup>2</sup>.
- Feed Pump: Reciprocating plunger type.
- Throttle Valve: Manually adjustable to vary nozzle inlet pressure.
- Thermometer: Digital type K, 0.1°C resolution, 12 way selector connected to 9 thermocouples.
- Pressure Gauges:
  - - Two, range 0 to 800 kNm<sup>-2</sup> to indicate refrigerant vapour generator and nozzle inlet pressure.
  - - Two, range – 100 to + 100 kNm<sup>-2</sup> to indicate evaporator and condenser pressure.
- Flow Meter: Variable area glass tube type. Range 0 to 75g s<sup>-1</sup>.
- Voltmeter and Ammeter: To measure power input to evaporator. Ranges 0 to 250V and 0 to 3A respectively.
- Pressure Relief Valves: Fitted to vapour generator, evaporator and condenser.
- High Pressure Cut Out: Fitted to vapour generator and condenser.
- Low Water Flow Switch: To switch off power supply if insufficient water flows through the condenser.
- Solenoid Valve: To isolate vapour generator from ejector, evaporator and condenser.
- High Temperature Cut Out: Fitted to all heater elements.
- All circuits are protected by a fuse.

#### Recommended Ancillaries

- F823S

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS

**What's in the Box?**

- 1 x R853
- 1 x Transformer (115V only)
- 1 x 3m Reinforced PVC tubing
- 1 x 3m PVC tube
- 1 x charging line and valve
- 9 x Spare 'o' rings
- 1 x Spare refrigerant can
- 1 x Power lead
- Instruction manual
- Packing list
- Test sheet

**Weights & Dimensions**

- Weight: 102 kg
- Weight: 106 kg (115V version)
- Length: 1060mm
- Width: 430mm
- Height: 925mm

**Essential Services**

- 2.5kW, 220-240 Volts Single Phase, 50Hz (With earth/ground).
- 2.5kW, 110-120 Volts Single Phase, 60Hz (With earth/ground).
- Water:
  - - 250 litres / hour at 15m head.
  - - Water temperature should not exceed 22°C if a useful range of test conditions are to be investigated.

**Ordering information**

To order this product, please call PA Hilton quoting the following codes:

R853/230

R853/115

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS