



ADDITIONAL 80W SOLAR PANEL RE540C



Year 1
study

Features

- Compact solar panel
- Extruded frame
- Castor wheels

Description

The optional additional solar panel is almost identical to the panel supplied with the base unit RE540. The only difference is that it is not fitted with a temperature sensor or solarimeter as it is assumed that it will be placed in the same solar conditions as the base unit.

The power outlet lead from the additional solar panel should be connected to one of the 3 additional connectors on the rear of the RE540 control console.

Related laws

- Increases RE540 capacity

- Demonstration
- Research

Technical Specification

- 12V, 80W nominal

Essential Ancillaries

- RE540

Recommended Ancillaries

- RE540A
- RE540B
- RE540D
- RE540E

What's in the Box?

- 1 x RE540C

- 1 x power outlet lead
- 1 x RE540 connecting plug
- Packing list
- Test sheet

You might also like

- RE540A
- RE540B
- RE540D
- RE540E

Weights & Dimensions

- Weight: 8 kg
- Length: 666mm
- Width: 34mm
- Height: 1152mm

Essential Services

- RE540

Operational Conditions

- Operating temperature range: -40°C to +85°C

Ordering information

To order this product, please call PA Hilton quoting the following code:

RE540C

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS