




## BENDING STRESS in a BEAM

### HST20



Year 2  
study

#### Features

- Only requires one HDA200 to view all key parameters.
- Span can be adjusted.
- Quick and easy installation of 'T' Beam.
- All wires terminated for quick connection.
- Potential for customer specific specimens.
- Dedicated e-book supplied

#### Description

An inverted aluminium T-beam is mounted between two simple supports on point contacts. The load onto the T-beam is applied using a screw jack mechanism with integral load cell. The load cell arrangement and supports create a three point loading. A number of precision strain gauges are accurately located on the T-beam specimen. These strain gauges are paired with temperature compensation dummy gauges for output stability. Each strain gauge pair is numbered for accurate connection to the HDA200 Interface (sold separately). The signals from the loading mechanism and strain gauges are fed directly into the HDA200 Interface (sold separately).

#### Related Laws/Applications

- Bending Stress.
- Strain.
- Strain Gauges.
- Bending Equation.
- Neutral Axis.
- Second Moment of Area.

#### Learning capabilities

- Comparison of theory with experimental results
- Working with Strain gauges
- Bending equation
- Neutral axis
- Working with stresses and strains and their conversion
- Second Moment of Area

## Technical Specification

- Beam: 900(L) x 51(H) x 25(W) x 3.2(t) mm
- Loading Mechanism: 0...500N
- Five pairs of strain gauges
- Half Bridge Strain Gauging

## Essential Ancillaries

- HST1 (or HST100)
- HDA200


## What's in the Box?

- 1 x Strain Gauged 'T' Beam
- 1 x Loading Mechanism
- 2 x Support Pillar
- 2 x Dowell Point Contact
- 1 x Tape measure
- Accessories container
- Hex wrench
- Instruction manual
- Software
- E-book
- Packing list
- Test sheet

## You might also like

- HST35
- HSM18

## Supporting Software



- HST20S

## Minimum System Requirements

- Computer or Laptop running WIN7 or above

## Weights & Dimensions

- Weight: 4 kg
- Length: 1000mm
- Width: 430mm
- Height: 120mm

## Essential Services

- 110/120V, 60Hz or 220/240V, 50Hz, single phase, live neutral and earth for HDA200

## Operational Conditions

- Storage temperature: -10°C to +70°C
- Operating temperature range: +10°C to +50°C
- Operating relative humidity range: 0 to 95%, non condensing

## Ordering information

To order this product, please call PA Hilton quoting the following code: HST20

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS