



WALL JIB CRANE HFC14



Year 1
study

Features

- Wall mounted apparatus.
- Can be mounted to HST1, HST100, HAC10, HAC14, HVT12f frames
- Crane with compression jib and tension tie
- Tension tie length adjustable
- Direct measurement and recording of forces
- Folds flat when not in use
- Full set of weights and hanger supplied

Description

This apparatus illustrates the application of a triangle of forces very clearly through the use of a wall jib crane. This self-contained jib crane has a vertical back support that supports a vertical rod. At the bottom of this rod is attached a swivel joint for the lower compression member. This joint swivels but cannot move vertically. At the upper end of the rod is a movable joint. This joint has a hook protruding and allows the attachment of a chain which itself is attached to the tension member of the crane. The ends of the compression and tension member are joined at a common point. A small pulley is attached at this point also, over which a cord passes, and terminates with the Load hanger. One end of the cord also attaches to a movable hook that runs vertically on the support rod. By adjusting the cord length, chain length and positions of the hooks, the lengths of the compression and tension members can be adjusted along with their angular positions. The forces in the compression member are read directly from the integral Newton scale. A compression spring of known spring rate is enclosed within the compression member. A spring balance is suspended between the chain and the pulley to measure the tensile forces in the tension member. After loading the member lengths can be adjusted to their 'zero load' lengths as part of the experimental procedure.

Related Laws/Applications

- Triangle of Forces
- Polygon of Forces
- Compression
- Tension
- Jib and Ties
- Structural Engineering
- Civil Engineering
- Cranes

Learning capabilities

- To determine the experimental values of the forces in the principal parts of the jib crane.
- To study the effect of altering the length of the tie to change the geometry.
- To compare the results with the forces obtained from graphical solutions using a polygon or a triangle of forces.

Technical Specification

- Maximum vertical distance between wall pivots approximately 350mm
- Tensile Member length: 500mm (approx.)
- Compressive Member length: 400mm (approx.)
- Tensile force spring balance 6Kgf in 0.1Kgf increments
- Compressive force spring balance: 60N in 2N increments
- Weights set: 3 x 5N
- 1 x Load hanger

Recommended Ancillaries

- HST1
- HST100
- HAC10
- HAC14
- HVT12f

What's in the Box?

- 1 x HFC14
- 1 x Load hanger
- 1 x Tape measure
- 3 x 5N
- 1 x 1m Spare cord
- 1 x 0.3m chain
- 1 x spring balance
- Instruction manual
- Packing list
- Test sheet

You might also like

- HFC15

Weights & Dimensions

- Weight: 2 kg
- Length: 570mm
- Width: 130mm
- Height: 100mm

Essential Services

- Sturdy vertical support

Ordering information

To order this product, please call PA Hilton quoting the following code: HFC14

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS